


Enviroment Variables



--



Beszel Environment Variables

Below is a comprehensive list of environment variables for both the Beszel Hub and the Agent. These variables control functionality such as content security policies, OAuth/OIDC behavior, filesystem monitoring, and more. For additional details, refer to the official [Beszel Environment Variables Guide](#).

Hub

| Name | Default | Description |
|------------------------------------|---------|--|
| <code>CSP</code> | unset | Adds a Content-Security-Policy header with this value. |
| <code>DISABLE_PASSWORD_AUTH</code> | false | Disables password authentication. |
| <code>USER_CREATION</code> | false | Enables automatic user creation for OAuth2 / OIDC. |

Agent

| Name | Default | Description |
|-------------------|---------|--|
| DOCKER_HOST | unset | Overrides the docker host (<code>docker.sock</code>) if using a proxy. Relevant when using linuxserver/docker-socket-proxy or similar. |
| EXTRA_FILESYSTEMS | unset | Monitor extra disks if using the binary agent. See Additional Disks . |
| FILESYSTEM | unset | Device, partition, or mount point to use for root disk stats. |
| KEY | unset | Public SSH key to use for authentication (provided by the Hub). |
| LOG_LEVEL | info | Logging level. Valid values: <code></code> |

Revision #3
Created 2 February 2025 11:00:47 by aeoneros
Updated 2 February 2025 11:20:13 by aeoneros