


# Enviroment Variables



--



## Beszel Environment Variables

Below is a comprehensive list of environment variables for both the Beszel Hub and the Agent. These variables control functionality such as content security policies, OAuth/OIDC behavior, filesystem monitoring, and more. For additional details, refer to the official [Beszel Environment Variables Guide](#).

### Hub

Name	Default	Description
<code>CSP</code>	unset	Adds a <a href="#">Content-Security-Policy</a> header with this value.
<code>DISABLE_PASSWORD_AUTH</code>	false	Disables password authentication.
<code>USER_CREATION</code>	false	Enables automatic user creation for OAuth2 / OIDC.

---

# Agent

Name	Default	Description
DOCKER_HOST	unset	Overrides the docker host ( <code>docker.sock</code> ) if using a proxy. Relevant when using <a href="#">linuxserver/docker-socket-proxy</a> or similar.
EXTRA_FILESYSTEMS	unset	Monitor extra disks if using the binary agent. See <a href="#">Additional Disks</a> .
FILESYSTEM	unset	Device, partition, or mount point to use for root disk stats.
KEY	unset	Public SSH key to use for authentication (provided by the Hub).
LOG_LEVEL	info	Logging level. Valid values: <code></code>

---

Revision #3  
Created 2 February 2025 11:00:47 by aeoneros  
Updated 2 February 2025 11:20:13 by aeoneros