

# Add 3rd Party Authentication (Google, Twitch etc.)



In the Following Wiki Article i will Provide you Informations on how to add SSO API's to your Linkwarden.

Here are all the SSO/OAuth integrations Linkwarden currently has. (10.10.2024)

Other than the [Authentik](#) and [Keycloak](#) integrations, most of the other integrations are **untested**. Please first backup your database, *just in case*.

To get support from the community, please visit our **Discord server**.

- [illegible]

•

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

### IMPORTANT

This is the Callback URL for your SSO-API's

<https://domain.tld/api/v1/auth/callback/servicename>

For Example:

<https://links.aeoneros.com/api/v1/auth/callback/discord>

## 42 School

The variables you need to configure to enable support for 42 School (OIDC):

| Environment Variable         | Default | Description  |
|------------------------------|---------|--|
| NEXT_PUBLIC_FORTYTWO_ENABLED | -       | If set to true, 42 School will be enabled and you'll need to define the variables below. |
| FORTYTWO_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| FORTYTWO_CLIENT_ID           | -       | Client ID  |
| FORTYTWO_CLIENT_SECRET       | -       | Client Secret.   |

## Apple

The variables you need to configure to enable support for Apple (OIDC):

| Environment Variable      | Default | Description  |
|---------------------------|---------|--|
| NEXT_PUBLIC_APPLE_ENABLED | -       | If set to true, Apple will be enabled and you'll need to define the variables below. |
| APPLE_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| APPLE_CLIENT_ID           | -       | Client ID  |
| APPLE_CLIENT_SECRET       | -       | Client Secret.   |

# Atlassian

The variables you need to configure to enable support for Atlassian (OIDC):

| Environment Variable          | Default | Description  |
|-------------------------------|---------|--|
| NEXT_PUBLIC_ATLASSIAN_ENABLED | -       | If set to true, Atlassian will be enabled and you'll need to define the variables below. |
| ATLASSIAN_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| ATLASSIAN_SCOPE               | -       | Optionally set a custom scope.   |
| ATLASSIAN_CLIENT_ID           | -       | Client ID  |
| ATLASSIAN_CLIENT_SECRET       | -       | Client Secret.   |

# Auth0

The variables you need to configure to enable support for Auth0 (OIDC):

| Environment Variable      | Default | Description  |
|---------------------------|---------|--|
| NEXT_PUBLIC_AUTH0_ENABLED | -       | If set to true, Auth0 will be enabled and you'll need to define the variables below. |
| AUTH0_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| AUTH0_ISSUER              | -       | Issuer.  |

| Environment Variable | Default | Description    |
|----------------------|---------|----------------|
| AUTH0_CLIENT_ID      | -       | Client ID      |
| AUTH0_CLIENT_SECRET  | -       | Client Secret. |

# Authelia

The variables you need to configure to enable support for Authelia (OIDC).

| Environment Variable         | Default | Description   |
|------------------------------|---------|---|
| NEXT_PUBLIC_AUTHELIA_ENABLED | -       | If set to true, Authelia will be enabled and you'll need to define the variables below. |
| AUTHELIA_WELLKNOWN_URL       | -       | https://{authelia.domain.com}/.well-known/openid-configuration                          |
| AUTHELIA_CLIENT_ID           | -       | Client ID   |
| AUTHELIA_CLIENT_SECRET       | -       | Client Secret. (Random Password from command below)                                     |

Generate the client secret with

```
docker exec -it authelia authelia crypto hash generate pbkdf2 --variant sha512 --random --random.length 72 --random.charset rfc3986
```

■ ■

The `Random Password` should be used for the `AUTHELIA_CLIENT_SECRET` variable in linkwarden & the `Digest` should be used for `client_secret` in th Authelia config below.

Authelia config should be as follows:

```
- client_id: linkwarden
  client_name: Linkwarden
  client_secret: {{Digest from command above}}
  public: false
  authorization_policy: one_factor
  consent_mode: implicit
  scopes:
    - openid
    - groups
    - email
```

```
- profile
redirect_uris:
- https://{linkwarden.domain.com}/api/v1/auth/callback/authelia
userinfo_signed_response_alg: none
```

■

# Authentik

The variables you need to configure to enable support for Authentik (OIDC):

| Environment Variable          | Default | Description   |
|-------------------------------|---------|---|
| NEXT_PUBLIC_AUTHENTIK_ENABLED | -       | If set to true, Authentik will be enabled and you'll need to define the variables below.  |
| AUTHENTIK_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| AUTHENTIK_ISSUER              | -       | This is the "OpenID Configuration Issuer" shown in the Provider Overview. Note that you must delete the "/" at the end of the URL. Should look like: <code>https://authentik.my-domain.in/application/o/linkwarden</code> |
| AUTHENTIK_CLIENT_ID           | -       | Client ID copied from the Provider Overview screen in Authentik   |
| AUTHENTIK_CLIENT_SECRET       | -       | Client Secret copied from the Provider Overview screen in Authentik   |

Administrators are required to also set the environment variable `NEXTAUTH_URL=https://linkwarden.my-domain.in/api/v1/auth` (during the linkwarden install process or docker ENV variables) and ensure a JWT signing key is selected in Authentik's Providers settings (this can be the default self-signed authentik certificate). Note that the Authentik Provider "Redirect URIs" section can be left blank, it will autofill with a URL after the first time it is used. The URL will look like: `https://linkwarden.my-domain.in/api/v1/auth/callback/authentik`

Authentik Setup Example:

Create a Provider on Authentik with the following settings:

Authentik Provider Settings

Create an Application with the following settings:

Authentik Application Settings

Finally, Assign users or groups of users to the application so they have access (Select the linkwarden application in Authentik, select the "Policy/Group/User Bindings" tab, then `Bind existing Policy` -> `Group` or `users` -> select either a group or a user):

Authentik User Access Settings

# Battle.net

The variables you need to configure to enable support for Battle.net (OIDC):

| Environment Variable          | Default | Description   |
|-------------------------------|---------|---|
| NEXT_PUBLIC_BATTLENET_ENABLED | -       | If set to true, Battle.net will be enabled and you'll need to define the variables below. |
| BATTLENET_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| BATTLENET_ISSUER              | -       | Issuer.   |
| BATTLENET_CLIENT_ID           | -       | Client ID   |
| BATTLENET_CLIENT_SECRET       | -       | Client Secret.  |

# Box

The variables you need to configure to enable support for Box (OIDC):

| Environment Variable    | Default | Description  |
|-------------------------|---------|--|
| NEXT_PUBLIC_BOX_ENABLED | -       | If set to true, Box will be enabled and you'll need to define the variables below. |
| BOX_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| BOX_ISSUER              | -       | Issuer.  |
| BOX_CLIENT_ID           | -       | Client ID  |
| BOX_CLIENT_SECRET       | -       | Client Secret.   |

# Bungie

The variables you need to configure to enable support for Bungie (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_BUNGIE_ENABLED | -       | If set to true, Bungie will be enabled and you'll need to define the variables below. |
| BUNGIE_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| BUNGIE_API_KEY             | -       | API Key.  |
| BUNGIE_CLIENT_ID           | -       | Client ID   |
| BUNGIE_CLIENT_SECRET       | -       | Client Secret.  |

# Cognito

The variables you need to configure to enable support for Cognito (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_COGNITO_ENABLED | -       | If set to true, Cognito will be enabled and you'll need to define the variables below. |
| COGNITO_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| COGNITO_ISSUER              | -       | Issuer.  |
| COGNITO_CLIENT_ID           | -       | Client ID  |
| COGNITO_CLIENT_SECRET       | -       | Client Secret.   |

# Coinbase

The variables you need to configure to enable support for Coinbase (OIDC):



| Environment Variable         | Default | Description   |
|------------------------------|---------|---|
| NEXT_PUBLIC_COINBASE_ENABLED | -       | If set to true, Coinbase will be enabled and you'll need to define the variables below. |
| COINBASE_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| COINBASE_CLIENT_ID           | -       | Client ID   |
| COINBASE_CLIENT_SECRET       | -       | Client Secret.  |

# Discord

The variables you need to configure to enable support for Discord (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_DISCORD_ENABLED | -       | If set to true, Discord will be enabled and you'll need to define the variables below. |
| DISCORD_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| DISCORD_CLIENT_ID           | -       | Client ID  |
| DISCORD_CLIENT_SECRET       | -       | Client Secret.   |

# Dropbox

The variables you need to configure to enable support for Dropbox (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_DROPBOX_ENABLED | -       | If set to true, Dropbox will be enabled and you'll need to define the variables below. |
| DROPBOX_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| DROPBOX_CLIENT_ID           | -       | Client ID  |
| DROPBOX_CLIENT_SECRET       | -       | Client Secret.   |

# Duende Identity Server 6

The variables you need to configure to enable support for Duende Identity Server 6 (OIDC):

| Environment Variable            | Default | Description   |
|---------------------------------|---------|---|
| NEXT_PUBLIC_DUENDE_IDS6_ENABLED | -       | If set to true, Duende Identity Server 6 will be enabled and you'll need to define the variables below. |
| DUENDE_IDS6_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| DUENDE_IDS6_ISSUER              | -       | Issuer.   |
| DUENDE_IDS6_CLIENT_ID           | -       | Client ID   |
| DUENDE_IDS6_CLIENT_SECRET       | -       | Client Secret.  |

# EVE Online

The variables you need to configure to enable support for EVE Online (OIDC):

| Environment Variable          | Default | Description   |
|-------------------------------|---------|---|
| NEXT_PUBLIC_EVEONLINE_ENABLED | -       | If set to true, EVE Online will be enabled and you'll need to define the variables below. |
| EVEONLINE_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| EVEONLINE_CLIENT_ID           | -       | Client ID   |
| EVEONLINE_CLIENT_SECRET       | -       | Client Secret.  |

# Facebook

The variables you need to configure to enable support for Facebook (OIDC):

| Environment Variable | Default | Description |
|----------------------|---------|-------------|
|----------------------|---------|-------------|

|                              |   |   |
|------------------------------|---|---|
| NEXT_PUBLIC_FACEBOOK_ENABLED | - | If set to true, Facebook will be enabled and you'll need to define the variables below. |
| FACEBOOK_CUSTOM_NAME         | - | Optionally set a custom provider name.  |
| FACEBOOK_CLIENT_ID           | - | Client ID   |
| FACEBOOK_CLIENT_SECRET       | - | Client Secret.  |

# FACEIT

The variables you need to configure to enable support for FACEIT (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_FACEIT_ENABLED | -       | If set to true, FACEIT will be enabled and you'll need to define the variables below. |
| FACEIT_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| FACEIT_CLIENT_ID           | -       | Client ID   |
| FACEIT_CLIENT_SECRET       | -       | Client Secret.  |

# Foursquare

The variables you need to configure to enable support for Foursquare (OIDC):

| Environment Variable           | Default | Description   |
|--------------------------------|---------|---|
| NEXT_PUBLIC_FOURSQUARE_ENABLED | -       | If set to true, Foursquare will be enabled and you'll need to define the variables below. |
| FOURSQUARE_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| FOURSQUARE_APIVERSION          | -       | API Version.  |
| FOURSQUARE_CLIENT_ID           | -       | Client ID   |
| FOURSQUARE_CLIENT_SECRET       | -       | Client Secret.  |

# Freshbooks

The variables you need to configure to enable support for Freshbooks (OIDC):

| Environment Variable           | Default | Description   |
|--------------------------------|---------|---|
| NEXT_PUBLIC_FRESHBOOKS_ENABLED | -       | If set to true, Freshbooks will be enabled and you'll need to define the variables below. |
| FRESHBOOKS_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| FRESHBOOKS_CLIENT_ID           | -       | Client ID   |
| FRESHBOOKS_CLIENT_SECRET       | -       | Client Secret.  |

# Fusionauth

The variables you need to configure to enable support for Fusionauth (OIDC):

| Environment Variable           | Default | Description   |
|--------------------------------|---------|---|
| NEXT_PUBLIC_FUSIONAUTH_ENABLED | -       | If set to true, Fusionauth will be enabled and you'll need to define the variables below. |
| FUSIONAUTH_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| FUSIONAUTH_ISSUER              | -       | Issuer.   |
| FUSIONAUTH_CLIENT_ID           | -       | Client ID   |
| FUSIONAUTH_CLIENT_SECRET       | -       | Client Secret.  |
| FUSIONAUTH_TENANT_ID           | -       | Tenant ID.  |

# Github

The variables you need to configure to enable support for Github (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_GITHUB_ENABLED | -       | If set to true, Github will be enabled and you'll need to define the variables below. |
| GITHUB_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| GITHUB_CLIENT_ID           | -       | Client ID   |
| GITHUB_CLIENT_SECRET       | -       | Client Secret.  |

# Gitlab

The variables you need to configure to enable support for Gitlab (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_GITLAB_ENABLED | -       | If set to true, Gitlab will be enabled and you'll need to define the variables below. |
| GITLAB_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| GITLAB_CLIENT_ID           | -       | Client ID   |
| GITLAB_CLIENT_SECRET       | -       | Client Secret.  |

# Google

The variables you need to configure to enable support for Google (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_GOOGLE_ENABLED | -       | If set to true, Google will be enabled and you'll need to define the variables below. |
| GOOGLE_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| GOOGLE_CLIENT_ID           | -       | Client ID   |
| GOOGLE_CLIENT_SECRET       | -       | Client Secret.  |

# Hubspot

The variables you need to configure to enable support for Hubspot (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_HUBSPOT_ENABLED | -       | If set to true, Hubspot will be enabled and you'll need to define the variables below. |
| HUBSPOT_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| HUBSPOT_CLIENT_ID           | -       | Client ID  |
| HUBSPOT_CLIENT_SECRET       | -       | Client Secret.   |

# IdentityServer4

The variables you need to configure to enable support for IdentityServer4 (OIDC):

| Environment Variable     | Default | Description  |
|--------------------------|---------|--|
| NEXT_PUBLIC_IDS4_ENABLED | -       | If set to true, IdentityServer4 will be enabled and you'll need to define the variables below. |
| IDS4_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| IDS4_ISSUER              | -       | Issuer.  |
| IDS4_CLIENT_ID           | -       | Client ID  |
| IDS4_CLIENT_SECRET       | -       | Client Secret.   |

# Kakao

The variables you need to configure to enable support for Kakao (OIDC):

| Environment Variable | Default | Description |
|----------------------|---------|-------------|
|----------------------|---------|-------------|

|                           |   |  |
|---------------------------|---|--|
| NEXT_PUBLIC_KAKAO_ENABLED | - | If set to true, Kakao will be enabled and you'll need to define the variables below. |
| KAKAO_CUSTOM_NAME         | - | Optionally set a custom provider name.   |
| KAKAO_CLIENT_ID           | - | Client ID  |
| KAKAO_CLIENT_SECRET       | - | Client Secret.   |

# Keycloak

The variables you need to configure to enable support for Keycloak (OIDC):

| Environment Variable         | Default | Description  |
|------------------------------|---------|--|
| NEXT_PUBLIC_KEYCLOAK_ENABLED | -       | If set to true, Keycloak will be enabled and you'll need to define the variables below.  |
| KEYCLOAK_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| KEYCLOAK_ISSUER              | -       | Issuer should include the realm – e.g. <a href="https://my-keycloak-domain.com/realms/My_Realm">https://my-keycloak-domain.com/realms/My_Realm</a> |
| KEYCLOAK_CLIENT_ID           | -       | The Keycloak client-id - can be obtained from Keycloak.  |
| KEYCLOAK_CLIENT_SECRET       | -       | Can be obtained from Keycloak.   |

# Line

The variables you need to configure to enable support for Line (OIDC):

| Environment Variable     | Default | Description   |
|--------------------------|---------|---|
| NEXT_PUBLIC_LINE_ENABLED | -       | If set to true, Line will be enabled and you'll need to define the variables below. |
| LINE_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |

| Environment Variable | Default | Description    |
|----------------------|---------|----------------|
| LINE_CLIENT_ID       | -       | Client ID      |
| LINE_CLIENT_SECRET   | -       | Client Secret. |

# LinkedIn

The variables you need to configure to enable support for LinkedIn (OIDC):

| Environment Variable         | Default | Description   |
|------------------------------|---------|---|
| NEXT_PUBLIC_LINKEDIN_ENABLED | -       | If set to true, LinkedIn will be enabled and you'll need to define the variables below. |
| LINKEDIN_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| LINKEDIN_CLIENT_ID           | -       | Client ID   |
| LINKEDIN_CLIENT_SECRET       | -       | Client Secret.  |

# Mailchimp

The variables you need to configure to enable support for Mailchimp (OIDC):

| Environment Variable          | Default | Description  |
|-------------------------------|---------|--|
| NEXT_PUBLIC_MAILCHIMP_ENABLED | -       | If set to true, Mailchimp will be enabled and you'll need to define the variables below. |
| MAILCHIMP_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| MAILCHIMP_CLIENT_ID           | -       | Client ID  |
| MAILCHIMP_CLIENT_SECRET       | -       | Client Secret.   |

# Mailru



The variables you need to configure to enable support for Mailru (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_MAILRU_ENABLED | -       | If set to true, Mailru will be enabled and you'll need to define the variables below. |
| MAILRU_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| MAILRU_CLIENT_ID           | -       | Client ID   |
| MAILRU_CLIENT_SECRET       | -       | Client Secret.  |

# Naver

The variables you need to configure to enable support for Naver (OIDC):

| Environment Variable      | Default | Description  |
|---------------------------|---------|--|
| NEXT_PUBLIC_NAVER_ENABLED | -       | If set to true, Naver will be enabled and you'll need to define the variables below. |
| NAVER_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| NAVER_CLIENT_ID           | -       | Client ID  |
| NAVER_CLIENT_SECRET       | -       | Client Secret.   |

# Netlify

The variables you need to configure to enable support for Netlify (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_NETLIFY_ENABLED | -       | If set to true, Netlify will be enabled and you'll need to define the variables below. |
| NETLIFY_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| NETLIFY_CLIENT_ID           | -       | Client ID  |

| Environment Variable  | Default | Description    |
|-----------------------|---------|----------------|
| NETLIFY_CLIENT_SECRET | -       | Client Secret. |

# Okta

The variables you need to configure to enable support for Okta (OIDC):

| Environment Variable     | Default | Description   |
|--------------------------|---------|---|
| NEXT_PUBLIC_OKTA_ENABLED | -       | If set to true, Okta will be enabled and you'll need to define the variables below. |
| OKTA_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| OKTA_ISSUER              | -       | Issuer.   |
| OKTA_CLIENT_ID           | -       | Client ID   |
| OKTA_CLIENT_SECRET       | -       | Client Secret.  |

# Onelogin

The variables you need to configure to enable support for Onelogin (OIDC):

| Environment Variable         | Default | Description   |
|------------------------------|---------|---|
| NEXT_PUBLIC_ONELOGIN_ENABLED | -       | If set to true, Onelogin will be enabled and you'll need to define the variables below. |
| ONELOGIN_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| ONELOGIN_ISSUER              | -       | Issuer.   |
| ONELOGIN_CLIENT_ID           | -       | Client ID   |
| ONELOGIN_CLIENT_SECRET       | -       | Client Secret.  |

# Osso

The variables you need to configure to enable support for Osso (OIDC):

| Environment Variable     | Default | Description   |
|--------------------------|---------|---|
| NEXT_PUBLIC_OSSO_ENABLED | -       | If set to true, Osso will be enabled and you'll need to define the variables below. |
| OSSO_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| OSSO_ISSUER              | -       | Issuer.   |
| OSSO_CLIENT_ID           | -       | Client ID   |
| OSSO_CLIENT_SECRET       | -       | Client Secret.  |

## osu!

The variables you need to configure to enable support for osu! (OIDC):

| Environment Variable    | Default | Description   |
|-------------------------|---------|---|
| NEXT_PUBLIC_OSU_ENABLED | -       | If set to true, osu! will be enabled and you'll need to define the variables below. |
| OSU_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| OSU_CLIENT_ID           | -       | Client ID   |
| OSU_CLIENT_SECRET       | -       | Client Secret.  |

## Patreon

The variables you need to configure to enable support for Patreon (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_PATREON_ENABLED | -       | If set to true, Patreon will be enabled and you'll need to define the variables below. |
| PATREON_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |

| Environment Variable  | Default | Description    |
|-----------------------|---------|----------------|
| PATREON_CLIENT_ID     | -       | Client ID      |
| PATREON_CLIENT_SECRET | -       | Client Secret. |

# Pinterest

The variables you need to configure to enable support for Pinterest (OIDC):

| Environment Variable          | Default | Description  |
|-------------------------------|---------|--|
| NEXT_PUBLIC_PINTEREST_ENABLED | -       | If set to true, Pinterest will be enabled and you'll need to define the variables below. |
| PINTEREST_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| PINTEREST_CLIENT_ID           | -       | Client ID  |
| PINTEREST_CLIENT_SECRET       | -       | Client Secret.   |

# Pipedrive

The variables you need to configure to enable support for Pipedrive (OIDC):

| Environment Variable          | Default | Description  |
|-------------------------------|---------|--|
| NEXT_PUBLIC_PIPEDRIVE_ENABLED | -       | If set to true, Pipedrive will be enabled and you'll need to define the variables below. |
| PIPEDRIVE_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| PIPEDRIVE_CLIENT_ID           | -       | Client ID  |
| PIPEDRIVE_CLIENT_SECRET       | -       | Client Secret.   |

# Reddit

The variables you need to configure to enable support for Reddit (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_REDDIT_ENABLED | -       | If set to true, Reddit will be enabled and you'll need to define the variables below. |
| REDDIT_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| REDDIT_CLIENT_ID           | -       | Client ID   |
| REDDIT_CLIENT_SECRET       | -       | Client Secret.  |

# Salesforce

The variables you need to configure to enable support for Salesforce (OIDC):

| Environment Variable           | Default | Description   |
|--------------------------------|---------|---|
| NEXT_PUBLIC_SALESFORCE_ENABLED | -       | If set to true, Salesforce will be enabled and you'll need to define the variables below. |
| SALESFORCE_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| SALESFORCE_CLIENT_ID           | -       | Client ID   |
| SALESFORCE_CLIENT_SECRET       | -       | Client Secret.  |

# Slack

The variables you need to configure to enable support for Slack (OIDC):

| Environment Variable      | Default | Description  |
|---------------------------|---------|--|
| NEXT_PUBLIC_SLACK_ENABLED | -       | If set to true, Slack will be enabled and you'll need to define the variables below. |
| SLACK_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| SLACK_CLIENT_ID           | -       | Client ID  |

| Environment Variable | Default | Description    |
|----------------------|---------|----------------|
| SLACK_CLIENT_SECRET  | -       | Client Secret. |

# Spotify

The variables you need to configure to enable support for Spotify (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_SPOTIFY_ENABLED | -       | If set to true, Spotify will be enabled and you'll need to define the variables below. |
| SPOTIFY_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| SPOTIFY_CLIENT_ID           | -       | Client ID  |
| SPOTIFY_CLIENT_SECRET       | -       | Client Secret.   |

# Strava

The variables you need to configure to enable support for Strava (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_STRAVA_ENABLED | -       | If set to true, Strava will be enabled and you'll need to define the variables below. |
| STRAVA_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| STRAVA_CLIENT_ID           | -       | Client ID   |
| STRAVA_CLIENT_SECRET       | -       | Client Secret.  |

# Todoist

The variables you need to configure to enable support for Todoist (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_TODOIST_ENABLED | -       | If set to true, Todoist will be enabled and you'll need to define the variables below. |
| TODOIST_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| TODOIST_CLIENT_ID           | -       | Client ID  |
| TODOIST_CLIENT_SECRET       | -       | Client Secret.   |

# Twitch

The variables you need to configure to enable support for Twitch (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_TWITCH_ENABLED | -       | If set to true, Twitch will be enabled and you'll need to define the variables below. |
| TWITCH_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| TWITCH_CLIENT_ID           | -       | Client ID   |
| TWITCH_CLIENT_SECRET       | -       | Client Secret.  |

# United Effects

The variables you need to configure to enable support for United Effects (OIDC):

| Environment Variable               | Default | Description   |
|------------------------------------|---------|---|
| NEXT_PUBLIC_UNITED_EFFECTS_ENABLED | -       | If set to true, United Effects will be enabled and you'll need to define the variables below. |
| UNITED_EFFECTS_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| UNITED_EFFECTS_ISSUER              | -       | Issuer.   |
| UNITED_EFFECTS_CLIENT_ID           | -       | Client ID   |

| Environment Variable         | Default | Description    |
|------------------------------|---------|----------------|
| UNITED_EFFECTS_CLIENT_SECRET | -       | Client Secret. |

## VK

The variables you need to configure to enable support for VK (OIDC):

| Environment Variable   | Default | Description   |
|------------------------|---------|---|
| NEXT_PUBLIC_VK_ENABLED | -       | If set to true, VK will be enabled and you'll need to define the variables below. |
| VK_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| VK_CLIENT_ID           | -       | Client ID   |
| VK_CLIENT_SECRET       | -       | Client Secret.  |

## Wikimedia

The variables you need to configure to enable support for Wikimedia (OIDC):

| Environment Variable          | Default | Description  |
|-------------------------------|---------|--|
| NEXT_PUBLIC_WIKIMEDIA_ENABLED | -       | If set to true, Wikimedia will be enabled and you'll need to define the variables below. |
| WIKIMEDIA_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| WIKIMEDIA_CLIENT_ID           | -       | Client ID  |
| WIKIMEDIA_CLIENT_SECRET       | -       | Client Secret.   |

## Wordpress.com

The variables you need to configure to enable support for Wordpress.com (OIDC):



| Environment Variable          | Default | Description  |
|-------------------------------|---------|--|
| NEXT_PUBLIC_WORDPRESS_ENABLED | -       | If set to true, Wordpress.com will be enabled and you'll need to define the variables below. |
| WORDPRESS_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| WORDPRESS_CLIENT_ID           | -       | Client ID  |
| WORDPRESS_CLIENT_SECRET       | -       | Client Secret.   |

# Yandex

The variables you need to configure to enable support for Yandex (OIDC):

| Environment Variable       | Default | Description   |
|----------------------------|---------|---|
| NEXT_PUBLIC_YANDEX_ENABLED | -       | If set to true, Yandex will be enabled and you'll need to define the variables below. |
| YANDEX_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| YANDEX_CLIENT_ID           | -       | Client ID   |
| YANDEX_CLIENT_SECRET       | -       | Client Secret.  |

# Zitadel

The variables you need to configure to enable support for Zitadel (OIDC):

| Environment Variable        | Default | Description  |
|-----------------------------|---------|--|
| NEXT_PUBLIC_ZITADEL_ENABLED | -       | If set to true, Zitadel will be enabled and you'll need to define the variables below. |
| ZITADEL_CUSTOM_NAME         | -       | Optionally set a custom provider name.   |
| ZITADEL_ISSUER              | -       | Issuer.  |
| ZITADEL_CLIENT_ID           | -       | Client ID  |

| Environment Variable  | Default | Description    |
|-----------------------|---------|----------------|
| ZITADEL_CLIENT_SECRET | -       | Client Secret. |

# Zoho

The variables you need to configure to enable support for Zoho (OIDC):

| Environment Variable     | Default | Description   |
|--------------------------|---------|---|
| NEXT_PUBLIC_ZOHO_ENABLED | -       | If set to true, Zoho will be enabled and you'll need to define the variables below. |
| ZOHO_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| ZOHO_CLIENT_ID           | -       | Client ID   |
| ZOHO_CLIENT_SECRET       | -       | Client Secret.  |

# Zoom

The variables you need to configure to enable support for Zoom (OIDC):

| Environment Variable     | Default | Description   |
|--------------------------|---------|---|
| NEXT_PUBLIC_ZOOM_ENABLED | -       | If set to true, Zoom will be enabled and you'll need to define the variables below. |
| ZOOM_CUSTOM_NAME         | -       | Optionally set a custom provider name.  |
| ZOOM_CLIENT_ID           | -       | Client ID   |
| ZOOM_CLIENT_SECRET       | -       | Client Secret.  |