

Add 3rd Party Authentication (Google, Twitch etc.)



In the Following Wiki Article i will Provide you Informations on how to add SSO API's to your Linkwarden.

Here are all the SSO/OAuth integrations Linkwarden currently has. (10.10.2024)

Other than the [Authentik](#) and [Keycloak](#) integrations, most of the other integrations are **untested**. Please first backup your database, *just in case*.

To get support from the community, please visit our **Discord server**.

- [illegible]

•

-
-
-
-
-
-
-
-
-

IMPORTANT

This is the Callback URL for your SSO-API's

<https://domain.tld/api/v1/auth/callback/servicename>

For Example:

<https://links.aeoneros.com/api/v1/auth/callback/discord>

42 School

The variables you need to configure to enable support for 42 School (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_FORTYTWO_ENABLED	-	If set to true, 42 School will be enabled and you'll need to define the variables below.
FORTYTWO_CUSTOM_NAME	-	Optionally set a custom provider name.
FORTYTWO_CLIENT_ID	-	Client ID
FORTYTWO_CLIENT_SECRET	-	Client Secret.

Apple

The variables you need to configure to enable support for Apple (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_APPLE_ENABLED	-	If set to true, Apple will be enabled and you'll need to define the variables below.
APPLE_CUSTOM_NAME	-	Optionally set a custom provider name.
APPLE_CLIENT_ID	-	Client ID
APPLE_CLIENT_SECRET	-	Client Secret.

Atlassian

The variables you need to configure to enable support for Atlassian (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_ATLASSIAN_ENABLED	-	If set to true, Atlassian will be enabled and you'll need to define the variables below.
ATLASSIAN_CUSTOM_NAME	-	Optionally set a custom provider name.
ATLASSIAN_SCOPE	-	Optionally set a custom scope.
ATLASSIAN_CLIENT_ID	-	Client ID
ATLASSIAN_CLIENT_SECRET	-	Client Secret.

Auth0

The variables you need to configure to enable support for Auth0 (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_AUTH0_ENABLED	-	If set to true, Auth0 will be enabled and you'll need to define the variables below.
AUTH0_CUSTOM_NAME	-	Optionally set a custom provider name.
AUTH0_ISSUER	-	Issuer.

Environment Variable	Default	Description
AUTH0_CLIENT_ID	-	Client ID
AUTH0_CLIENT_SECRET	-	Client Secret.

Authelia

The variables you need to configure to enable support for Authelia (OIDC).

Environment Variable	Default	Description
NEXT_PUBLIC_AUTHELIA_ENABLED	-	If set to true, Authelia will be enabled and you'll need to define the variables below.
AUTHELIA_WELLKNOWN_URL	-	https://{authelia.domain.com}/.well-known/openid-configuration
AUTHELIA_CLIENT_ID	-	Client ID
AUTHELIA_CLIENT_SECRET	-	Client Secret. (Random Password from command below)

Generate the client secret with

```
docker exec -it authelia authelia crypto hash generate pbkdf2 --variant sha512 --random --random.length 72 --random.charset rfc3986
```

■ ■

The `Random Password` should be used for the `AUTHELIA_CLIENT_SECRET` variable in linkwarden & the `Digest` should be used for `client_secret` in th Authelia config below.

Authelia config should be as follows:

```
- client_id: linkwarden
  client_name: Linkwarden
  client_secret: {{Digest from command above}}
  public: false
  authorization_policy: one_factor
  consent_mode: implicit
  scopes:
    - openid
    - groups
    - email
```

```
- profile
redirect_uris:
- https://{linkwarden.domain.com}/api/v1/auth/callback/authelia
userinfo_signed_response_alg: none
```

■

Authentik

The variables you need to configure to enable support for Authentik (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_AUTHENTIK_ENABLED	-	If set to true, Authentik will be enabled and you'll need to define the variables below.
AUTHENTIK_CUSTOM_NAME	-	Optionally set a custom provider name.
AUTHENTIK_ISSUER	-	This is the "OpenID Configuration Issuer" shown in the Provider Overview. Note that you must delete the "/" at the end of the URL. Should look like: <code>https://authentik.my-domain.in/application/o/linkwarden</code>
AUTHENTIK_CLIENT_ID	-	Client ID copied from the Provider Overview screen in Authentik
AUTHENTIK_CLIENT_SECRET	-	Client Secret copied from the Provider Overview screen in Authentik

Administrators are required to also set the environment variable `NEXTAUTH_URL=https://linkwarden.my-domain.in/api/v1/auth` (during the linkwarden install process or docker ENV variables) and ensure a JWT signing key is selected in Authentik's Providers settings (this can be the default self-signed authentik certificate). Note that the Authentik Provider "Redirect URIs" section can be left blank, it will autofill with a URL after the first time it is used. The URL will look like: `https://linkwarden.my-domain.in/api/v1/auth/callback/authentik`

Authentik Setup Example:

Create a Provider on Authentik with the following settings:

Authentik Provider Settings

Create an Application with the following settings:

Authentik Application Settings

Finally, Assign users or groups of users to the application so they have access (Select the linkwarden application in Authentik, select the "Policy/Group/User Bindings" tab, then `Bind existing Policy` -> `Group` or `users` -> select either a group or a user):

Authentik User Access Settings

Battle.net

The variables you need to configure to enable support for Battle.net (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_BATTLENET_ENABLED	-	If set to true, Battle.net will be enabled and you'll need to define the variables below.
BATTLENET_CUSTOM_NAME	-	Optionally set a custom provider name.
BATTLENET_ISSUER	-	Issuer.
BATTLENET_CLIENT_ID	-	Client ID
BATTLENET_CLIENT_SECRET	-	Client Secret.

Box

The variables you need to configure to enable support for Box (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_BOX_ENABLED	-	If set to true, Box will be enabled and you'll need to define the variables below.
BOX_CUSTOM_NAME	-	Optionally set a custom provider name.
BOX_ISSUER	-	Issuer.
BOX_CLIENT_ID	-	Client ID
BOX_CLIENT_SECRET	-	Client Secret.

Bungie

The variables you need to configure to enable support for Bungie (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_BUNGIE_ENABLED	-	If set to true, Bungie will be enabled and you'll need to define the variables below.
BUNGIE_CUSTOM_NAME	-	Optionally set a custom provider name.
BUNGIE_API_KEY	-	API Key.
BUNGIE_CLIENT_ID	-	Client ID
BUNGIE_CLIENT_SECRET	-	Client Secret.

Cognito

The variables you need to configure to enable support for Cognito (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_COGNITO_ENABLED	-	If set to true, Cognito will be enabled and you'll need to define the variables below.
COGNITO_CUSTOM_NAME	-	Optionally set a custom provider name.
COGNITO_ISSUER	-	Issuer.
COGNITO_CLIENT_ID	-	Client ID
COGNITO_CLIENT_SECRET	-	Client Secret.

Coinbase

The variables you need to configure to enable support for Coinbase (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_COINBASE_ENABLED	-	If set to true, Coinbase will be enabled and you'll need to define the variables below.
COINBASE_CUSTOM_NAME	-	Optionally set a custom provider name.
COINBASE_CLIENT_ID	-	Client ID
COINBASE_CLIENT_SECRET	-	Client Secret.

Discord

The variables you need to configure to enable support for Discord (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_DISCORD_ENABLED	-	If set to true, Discord will be enabled and you'll need to define the variables below.
DISCORD_CUSTOM_NAME	-	Optionally set a custom provider name.
DISCORD_CLIENT_ID	-	Client ID
DISCORD_CLIENT_SECRET	-	Client Secret.

Dropbox

The variables you need to configure to enable support for Dropbox (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_DROPBOX_ENABLED	-	If set to true, Dropbox will be enabled and you'll need to define the variables below.
DROPBOX_CUSTOM_NAME	-	Optionally set a custom provider name.
DROPBOX_CLIENT_ID	-	Client ID
DROPBOX_CLIENT_SECRET	-	Client Secret.

Duende Identity Server 6

The variables you need to configure to enable support for Duende Identity Server 6 (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_DUENDE_IDS6_ENABLED	-	If set to true, Duende Identity Server 6 will be enabled and you'll need to define the variables below.
DUENDE_IDS6_CUSTOM_NAME	-	Optionally set a custom provider name.
DUENDE_IDS6_ISSUER	-	Issuer.
DUENDE_IDS6_CLIENT_ID	-	Client ID
DUENDE_IDS6_CLIENT_SECRET	-	Client Secret.

EVE Online

The variables you need to configure to enable support for EVE Online (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_EVEONLINE_ENABLED	-	If set to true, EVE Online will be enabled and you'll need to define the variables below.
EVEONLINE_CUSTOM_NAME	-	Optionally set a custom provider name.
EVEONLINE_CLIENT_ID	-	Client ID
EVEONLINE_CLIENT_SECRET	-	Client Secret.

Facebook

The variables you need to configure to enable support for Facebook (OIDC):

Environment Variable	Default	Description
----------------------	---------	-------------

NEXT_PUBLIC_FACEBOOK_ENABLED	-	If set to true, Facebook will be enabled and you'll need to define the variables below.
FACEBOOK_CUSTOM_NAME	-	Optionally set a custom provider name.
FACEBOOK_CLIENT_ID	-	Client ID
FACEBOOK_CLIENT_SECRET	-	Client Secret.

FACEIT

The variables you need to configure to enable support for FACEIT (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_FACEIT_ENABLED	-	If set to true, FACEIT will be enabled and you'll need to define the variables below.
FACEIT_CUSTOM_NAME	-	Optionally set a custom provider name.
FACEIT_CLIENT_ID	-	Client ID
FACEIT_CLIENT_SECRET	-	Client Secret.

Foursquare

The variables you need to configure to enable support for Foursquare (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_FOURSQUARE_ENABLED	-	If set to true, Foursquare will be enabled and you'll need to define the variables below.
FOURSQUARE_CUSTOM_NAME	-	Optionally set a custom provider name.
FOURSQUARE_APIVERSION	-	API Version.
FOURSQUARE_CLIENT_ID	-	Client ID
FOURSQUARE_CLIENT_SECRET	-	Client Secret.

Freshbooks

The variables you need to configure to enable support for Freshbooks (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_FRESHBOOKS_ENABLED	-	If set to true, Freshbooks will be enabled and you'll need to define the variables below.
FRESHBOOKS_CUSTOM_NAME	-	Optionally set a custom provider name.
FRESHBOOKS_CLIENT_ID	-	Client ID
FRESHBOOKS_CLIENT_SECRET	-	Client Secret.

Fusionauth

The variables you need to configure to enable support for Fusionauth (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_FUSIONAUTH_ENABLED	-	If set to true, Fusionauth will be enabled and you'll need to define the variables below.
FUSIONAUTH_CUSTOM_NAME	-	Optionally set a custom provider name.
FUSIONAUTH_ISSUER	-	Issuer.
FUSIONAUTH_CLIENT_ID	-	Client ID
FUSIONAUTH_CLIENT_SECRET	-	Client Secret.
FUSIONAUTH_TENANT_ID	-	Tenant ID.

Github

The variables you need to configure to enable support for Github (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_GITHUB_ENABLED	-	If set to true, Github will be enabled and you'll need to define the variables below.
GITHUB_CUSTOM_NAME	-	Optionally set a custom provider name.
GITHUB_CLIENT_ID	-	Client ID
GITHUB_CLIENT_SECRET	-	Client Secret.

Gitlab

The variables you need to configure to enable support for Gitlab (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_GITLAB_ENABLED	-	If set to true, Gitlab will be enabled and you'll need to define the variables below.
GITLAB_CUSTOM_NAME	-	Optionally set a custom provider name.
GITLAB_CLIENT_ID	-	Client ID
GITLAB_CLIENT_SECRET	-	Client Secret.

Google

The variables you need to configure to enable support for Google (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_GOOGLE_ENABLED	-	If set to true, Google will be enabled and you'll need to define the variables below.
GOOGLE_CUSTOM_NAME	-	Optionally set a custom provider name.
GOOGLE_CLIENT_ID	-	Client ID
GOOGLE_CLIENT_SECRET	-	Client Secret.

Hubspot

The variables you need to configure to enable support for Hubspot (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_HUBSPOT_ENABLED	-	If set to true, Hubspot will be enabled and you'll need to define the variables below.
HUBSPOT_CUSTOM_NAME	-	Optionally set a custom provider name.
HUBSPOT_CLIENT_ID	-	Client ID
HUBSPOT_CLIENT_SECRET	-	Client Secret.

IdentityServer4

The variables you need to configure to enable support for IdentityServer4 (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_IDS4_ENABLED	-	If set to true, IdentityServer4 will be enabled and you'll need to define the variables below.
IDS4_CUSTOM_NAME	-	Optionally set a custom provider name.
IDS4_ISSUER	-	Issuer.
IDS4_CLIENT_ID	-	Client ID
IDS4_CLIENT_SECRET	-	Client Secret.

Kakao

The variables you need to configure to enable support for Kakao (OIDC):

Environment Variable	Default	Description
----------------------	---------	-------------

NEXT_PUBLIC_KAKAO_ENABLED	-	If set to true, Kakao will be enabled and you'll need to define the variables below.
KAKAO_CUSTOM_NAME	-	Optionally set a custom provider name.
KAKAO_CLIENT_ID	-	Client ID
KAKAO_CLIENT_SECRET	-	Client Secret.

Keycloak

The variables you need to configure to enable support for Keycloak (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_KEYCLOAK_ENABLED	-	If set to true, Keycloak will be enabled and you'll need to define the variables below.
KEYCLOAK_CUSTOM_NAME	-	Optionally set a custom provider name.
KEYCLOAK_ISSUER	-	Issuer should include the realm – e.g. https://my-keycloak-domain.com/realms/My_Realm
KEYCLOAK_CLIENT_ID	-	The Keycloak client-id - can be obtained from Keycloak.
KEYCLOAK_CLIENT_SECRET	-	Can be obtained from Keycloak.

Line

The variables you need to configure to enable support for Line (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_LINE_ENABLED	-	If set to true, Line will be enabled and you'll need to define the variables below.
LINE_CUSTOM_NAME	-	Optionally set a custom provider name.

Environment Variable	Default	Description
LINE_CLIENT_ID	-	Client ID
LINE_CLIENT_SECRET	-	Client Secret.

LinkedIn

The variables you need to configure to enable support for LinkedIn (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_LINKEDIN_ENABLED	-	If set to true, LinkedIn will be enabled and you'll need to define the variables below.
LINKEDIN_CUSTOM_NAME	-	Optionally set a custom provider name.
LINKEDIN_CLIENT_ID	-	Client ID
LINKEDIN_CLIENT_SECRET	-	Client Secret.

Mailchimp

The variables you need to configure to enable support for Mailchimp (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_MAILCHIMP_ENABLED	-	If set to true, Mailchimp will be enabled and you'll need to define the variables below.
MAILCHIMP_CUSTOM_NAME	-	Optionally set a custom provider name.
MAILCHIMP_CLIENT_ID	-	Client ID
MAILCHIMP_CLIENT_SECRET	-	Client Secret.

Mailru

The variables you need to configure to enable support for Mailru (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_MAILRU_ENABLED	-	If set to true, Mailru will be enabled and you'll need to define the variables below.
MAILRU_CUSTOM_NAME	-	Optionally set a custom provider name.
MAILRU_CLIENT_ID	-	Client ID
MAILRU_CLIENT_SECRET	-	Client Secret.

Naver

The variables you need to configure to enable support for Naver (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_NAVER_ENABLED	-	If set to true, Naver will be enabled and you'll need to define the variables below.
NAVER_CUSTOM_NAME	-	Optionally set a custom provider name.
NAVER_CLIENT_ID	-	Client ID
NAVER_CLIENT_SECRET	-	Client Secret.

Netlify

The variables you need to configure to enable support for Netlify (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_NETLIFY_ENABLED	-	If set to true, Netlify will be enabled and you'll need to define the variables below.
NETLIFY_CUSTOM_NAME	-	Optionally set a custom provider name.
NETLIFY_CLIENT_ID	-	Client ID

Environment Variable	Default	Description
NETLIFY_CLIENT_SECRET	-	Client Secret.

Okta

The variables you need to configure to enable support for Okta (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_OKTA_ENABLED	-	If set to true, Okta will be enabled and you'll need to define the variables below.
OKTA_CUSTOM_NAME	-	Optionally set a custom provider name.
OKTA_ISSUER	-	Issuer.
OKTA_CLIENT_ID	-	Client ID
OKTA_CLIENT_SECRET	-	Client Secret.

Onelogin

The variables you need to configure to enable support for Onelogin (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_ONELOGIN_ENABLED	-	If set to true, Onelogin will be enabled and you'll need to define the variables below.
ONELOGIN_CUSTOM_NAME	-	Optionally set a custom provider name.
ONELOGIN_ISSUER	-	Issuer.
ONELOGIN_CLIENT_ID	-	Client ID
ONELOGIN_CLIENT_SECRET	-	Client Secret.

Osso

The variables you need to configure to enable support for Osso (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_OSSO_ENABLED	-	If set to true, Osso will be enabled and you'll need to define the variables below.
OSSO_CUSTOM_NAME	-	Optionally set a custom provider name.
OSSO_ISSUER	-	Issuer.
OSSO_CLIENT_ID	-	Client ID
OSSO_CLIENT_SECRET	-	Client Secret.

osu!

The variables you need to configure to enable support for osu! (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_OSU_ENABLED	-	If set to true, osu! will be enabled and you'll need to define the variables below.
OSU_CUSTOM_NAME	-	Optionally set a custom provider name.
OSU_CLIENT_ID	-	Client ID
OSU_CLIENT_SECRET	-	Client Secret.

Patreon

The variables you need to configure to enable support for Patreon (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_PATREON_ENABLED	-	If set to true, Patreon will be enabled and you'll need to define the variables below.
PATREON_CUSTOM_NAME	-	Optionally set a custom provider name.

Environment Variable	Default	Description
PATREON_CLIENT_ID	-	Client ID
PATREON_CLIENT_SECRET	-	Client Secret.

Pinterest

The variables you need to configure to enable support for Pinterest (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_PINTEREST_ENABLED	-	If set to true, Pinterest will be enabled and you'll need to define the variables below.
PINTEREST_CUSTOM_NAME	-	Optionally set a custom provider name.
PINTEREST_CLIENT_ID	-	Client ID
PINTEREST_CLIENT_SECRET	-	Client Secret.

Pipedrive

The variables you need to configure to enable support for Pipedrive (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_PIPEDRIVE_ENABLED	-	If set to true, Pipedrive will be enabled and you'll need to define the variables below.
PIPEDRIVE_CUSTOM_NAME	-	Optionally set a custom provider name.
PIPEDRIVE_CLIENT_ID	-	Client ID
PIPEDRIVE_CLIENT_SECRET	-	Client Secret.

Reddit

The variables you need to configure to enable support for Reddit (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_REDDIT_ENABLED	-	If set to true, Reddit will be enabled and you'll need to define the variables below.
REDDIT_CUSTOM_NAME	-	Optionally set a custom provider name.
REDDIT_CLIENT_ID	-	Client ID
REDDIT_CLIENT_SECRET	-	Client Secret.

Salesforce

The variables you need to configure to enable support for Salesforce (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_SALESFORCE_ENABLED	-	If set to true, Salesforce will be enabled and you'll need to define the variables below.
SALESFORCE_CUSTOM_NAME	-	Optionally set a custom provider name.
SALESFORCE_CLIENT_ID	-	Client ID
SALESFORCE_CLIENT_SECRET	-	Client Secret.

Slack

The variables you need to configure to enable support for Slack (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_SLACK_ENABLED	-	If set to true, Slack will be enabled and you'll need to define the variables below.
SLACK_CUSTOM_NAME	-	Optionally set a custom provider name.
SLACK_CLIENT_ID	-	Client ID

Environment Variable	Default	Description
SLACK_CLIENT_SECRET	-	Client Secret.

Spotify

The variables you need to configure to enable support for Spotify (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_SPOTIFY_ENABLED	-	If set to true, Spotify will be enabled and you'll need to define the variables below.
SPOTIFY_CUSTOM_NAME	-	Optionally set a custom provider name.
SPOTIFY_CLIENT_ID	-	Client ID
SPOTIFY_CLIENT_SECRET	-	Client Secret.

Strava

The variables you need to configure to enable support for Strava (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_STRAVA_ENABLED	-	If set to true, Strava will be enabled and you'll need to define the variables below.
STRAVA_CUSTOM_NAME	-	Optionally set a custom provider name.
STRAVA_CLIENT_ID	-	Client ID
STRAVA_CLIENT_SECRET	-	Client Secret.

Todoist

The variables you need to configure to enable support for Todoist (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_TODOIST_ENABLED	-	If set to true, Todoist will be enabled and you'll need to define the variables below.
TODOIST_CUSTOM_NAME	-	Optionally set a custom provider name.
TODOIST_CLIENT_ID	-	Client ID
TODOIST_CLIENT_SECRET	-	Client Secret.

Twitch

The variables you need to configure to enable support for Twitch (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_TWITCH_ENABLED	-	If set to true, Twitch will be enabled and you'll need to define the variables below.
TWITCH_CUSTOM_NAME	-	Optionally set a custom provider name.
TWITCH_CLIENT_ID	-	Client ID
TWITCH_CLIENT_SECRET	-	Client Secret.

United Effects

The variables you need to configure to enable support for United Effects (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_UNITED_EFFECTS_ENABLED	-	If set to true, United Effects will be enabled and you'll need to define the variables below.
UNITED_EFFECTS_CUSTOM_NAME	-	Optionally set a custom provider name.
UNITED_EFFECTS_ISSUER	-	Issuer.
UNITED_EFFECTS_CLIENT_ID	-	Client ID

Environment Variable	Default	Description
UNITED_EFFECTS_CLIENT_SECRET	-	Client Secret.

VK

The variables you need to configure to enable support for VK (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_VK_ENABLED	-	If set to true, VK will be enabled and you'll need to define the variables below.
VK_CUSTOM_NAME	-	Optionally set a custom provider name.
VK_CLIENT_ID	-	Client ID
VK_CLIENT_SECRET	-	Client Secret.

Wikimedia

The variables you need to configure to enable support for Wikimedia (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_WIKIMEDIA_ENABLED	-	If set to true, Wikimedia will be enabled and you'll need to define the variables below.
WIKIMEDIA_CUSTOM_NAME	-	Optionally set a custom provider name.
WIKIMEDIA_CLIENT_ID	-	Client ID
WIKIMEDIA_CLIENT_SECRET	-	Client Secret.

Wordpress.com

The variables you need to configure to enable support for Wordpress.com (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_WORDPRESS_ENABLED	-	If set to true, Wordpress.com will be enabled and you'll need to define the variables below.
WORDPRESS_CUSTOM_NAME	-	Optionally set a custom provider name.
WORDPRESS_CLIENT_ID	-	Client ID
WORDPRESS_CLIENT_SECRET	-	Client Secret.

Yandex

The variables you need to configure to enable support for Yandex (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_YANDEX_ENABLED	-	If set to true, Yandex will be enabled and you'll need to define the variables below.
YANDEX_CUSTOM_NAME	-	Optionally set a custom provider name.
YANDEX_CLIENT_ID	-	Client ID
YANDEX_CLIENT_SECRET	-	Client Secret.

Zitadel

The variables you need to configure to enable support for Zitadel (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_ZITADEL_ENABLED	-	If set to true, Zitadel will be enabled and you'll need to define the variables below.
ZITADEL_CUSTOM_NAME	-	Optionally set a custom provider name.
ZITADEL_ISSUER	-	Issuer.
ZITADEL_CLIENT_ID	-	Client ID

Environment Variable	Default	Description
ZITADEL_CLIENT_SECRET	-	Client Secret.

Zoho

The variables you need to configure to enable support for Zoho (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_ZOHO_ENABLED	-	If set to true, Zoho will be enabled and you'll need to define the variables below.
ZOHO_CUSTOM_NAME	-	Optionally set a custom provider name.
ZOHO_CLIENT_ID	-	Client ID
ZOHO_CLIENT_SECRET	-	Client Secret.

Zoom

The variables you need to configure to enable support for Zoom (OIDC):

Environment Variable	Default	Description
NEXT_PUBLIC_ZOOM_ENABLED	-	If set to true, Zoom will be enabled and you'll need to define the variables below.
ZOOM_CUSTOM_NAME	-	Optionally set a custom provider name.
ZOOM_CLIENT_ID	-	Client ID
ZOOM_CLIENT_SECRET	-	Client Secret.

Revision #4

Created 10 October 2024 16:05:36 by aeoneros

Updated 10 October 2024 16:32:13 by aeoneros