

Enviroment Variables

Environment Variable	Description	Example Value
SLEEP_TIME	Time interval between update checks (default: 5 minutes)	5m
IGNORELIST_SERVICES	Space-separated list of services to ignore during updates	shepherd my-other-service
FILTER_SERVICES	Filter for specifying services to update (matches docker service ls filter)	label=com.mydomain.autodeploy
ROLLBACK_ON_FAILURE	Roll back a service to the previous version if an update fails	true
UPDATE_OPTIONS	Additional options for the docker service update command	--update-delay=30s
TIMEOUT	Timeout for the docker service update process (default: 5 minutes)	300
APPRISE_SIDE CAR_URL	URL for the Apprise sidecar service to enable update notifications	apprise-microservice:5000
IMAGE_AUTOCLEAN_LIMIT	Enable old image autocleaning on service update	5
RUN_ONCE_AND_EXIT	Run Shepherd once and then exit	true
WITH_REGISTRY_AUTH	Enable private registry authentication	true
REGISTRY_USER / REGISTRY_PASSWORD	Credentials for private registry authentication	user123 / secret_password
REGISTRIES_FILE	Path to the secret file containing multiple registry authentication entries	/var/run/secrets/shepherd-registries-auth
WITH_INSECURE_REGISTRY	Enable connection to an insecure private registry	true
WITH_NO_RESOLVE_IMAGE	Prevent pulling images from the registry	true
TZ	Set the timezone for log entries	Europe/Zurich

Revision #2

Created 11 February 2025 15:32:32 by aeoneros

Updated 11 February 2025 15:33:25 by aeoneros